



Electrical Specification
 Rated voltage : 40 VAC
 Rated Current : 5AMP
 Contact Resistance : 30mΩ MAX.
 Insulation Resistance : 1000MΩ MIN.at 500V DC
 Withstanding voltage : 500V AC RMS for 1Minute
 Temperature range : -25C°- +85C°

| 6 | RIVET | 2 | BRASS | Ni |
|-----|-------------|-----|------------|----------------------------|
| 5 | COVER | 1 | PBT+30%G/F | Black |
| 4 | HARPOON | 2 | BRASS | Tin |
| 3 | SHELL | 1 | SPCC | Ni |
| 2 | CONTACT | 9 | BRASS | Gold Flash On Contact Area |
| 1 | INSULATOR | 1 | PBT+30%G/F | Black |
| NO. | DESCRIPTION | QTY | MATERIAL | TREATMENT |



| | | | | | | |
|-------------------|--|----------------|-------------------------|-----------|--------------|-----------|
| <i>Title</i> | D-SUB 9P Female DIP 90° 8.08mm Riveting With Harpoon | | | | | |
| <i>Tolerances</i> | <i>Drawer</i> | <i>Naomi</i> | <i>Part No:</i> | | | |
| <i>Linear</i> | <i>Checked</i> | <i>Summer</i> | WCT-DSC-DR9F00M5 | | | |
| <i>X ±0.15</i> | <i>Approved</i> | <i>Macus</i> | <i>Cus. Part No:</i> | | | |
| <i>.X ±0.05</i> | <i>Date</i> | 2017.07.03 | WCT-DSC-DR9F00M5 | | | |
| <i>Angles</i> | <i>Projection</i> | <i>Version</i> | <i>Size</i> | <i>A4</i> | <i>Units</i> | <i>mm</i> |
| ± 3° | | A | <i>Scale</i> | 1:1 | <i>Sheet</i> | 1/1 |